



900265 87DB-8-T

Hydraulic BF System

Powder-Coated



Used For

- Fluids with large quantities of larger particles (bag filter)
- Hydraulic Oil
- Transmissions Oil
- Other low viscosity oil
- Use with petroleum or synthetic fluids

Capacity, Sump Size & Flow Rate

- Requires 60 Qt./227.1 L. of makeup fluid (housing volume)
- **Cold oil sump range: 74-300 Gal./280.1-1135.6 L.
- **Warm oil sump range: 145-520 Gal./548.9-1968.4 L.
- **Hot oil sump range: 330-680 Gal./1249.2-2574.1 L.
- *Flow rate range for ISO: **10-32** from 1.9-6.5 GPM/7.2-24.6 LPM
- *Flow rate range for ISO **46-150** from 1.38-3.0 GPM/5.2-11.4 LPM

Other Specifications

- 8 GPM 65 PSI pump (*not fluid flow rate*)
- 3/4 HP 1725 RPM motor (TEFC)
- 120 volt, single phase
- 12' heavy duty power cord
- PSI switch low limit-12, high limit-65
- Pressure gauge
- Push sample port (*located on back panel*)
- Transfer valve
- Hoses
 - Suction-3/4" ID x 10' (3/4" male NPT x 3/4" female JIC)
 - Discharge-5/8" ID x 10' (3/4" male NPT x 5/8" female JIC)
- Max operating pressure 80 PSI
- **Optimal running pressure between 20-50 PSI (change filter when 50-60 PSI) - **NEW go-no-go gauge for indicating element change**

Overall Dimensions

- 46" (H) *Plus 20" Clearance above to remove filter*
- 23" (W)
- 23" (D)
- 232 lbs./105.2 kg. shipping weight

Notes

- **Flow rates are established using ISO 10-150 viscosity oils at the standard 40° C/104° F and are subject to vary
- **Viscosity, operating temperature, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, elements need to be changed between 300-1000 hours for optimal performance, ideally change the element when the flow is half the starting flow or the PSI is double the starting PSI
- Available in stainless-steel
- Available option for water-based lubricants
- Other system configurations are available

Recommended Elements

- X2 Model 1002 for ISO: 10, 15, 22, 32
- X2 Model 1004 for ISO: 46, 68, 100, 150

Note: All bag filters listed below go in front of the depth media filter to capture a larger quantity of contaminants before polishing the oil to a finer degree by the depth media filter

- Disposable bag filter models follow: **566** (5 micron), **567** (10 micron), **568** (15 micron), **569** (25 micron), **570** (50 micron), **571** (75 micron), **572** (100 micron), **3617** (150 micron), **3892** (200 micron), any customizable 3-layer back of your choice

Harvard Corporation is able to meet many custom requirements, please contact us with you specific custom needs