

4706 Element Water Glycol Element



Description

- Removes contaminants as low as 1-micron
- Removes particles from water-based coolants
- Does not remove or deplete additives

Used For

- Water Glycol Fluids
- All Water-Based Lubricants
- Special Oil-Based Application—***Upon Request

Capacity & Flow Rate

- Requires 12 Qt./11.4 L. of makeup fluid (housing volume)
- *Ideal coolant sump range from 0-50 Gal./0-189.3 L.
- **Flow rate range from 0-2 GPM/0-7.6 LPM

Specifications

- Beta₃=350
- Max operating pressure 80 PSI
- Overall dimensions 10" (H), 7.5" (D)
- Fits part # 900057
- Used with water-based fluids or, if applicable, petroleum or synthetic fluids

Notes

- **Flow rates are established using ISO 46-150 viscosity oils at the standard 40° C/104° F and are subject to vary
- *Viscosity, operating temperature, and generated contamination will affect sizing and flow rates of filtration equipment
- Most applications, elements need to be changed between 500-1000 hours for optimal performance, ideally change the element when the flow is half the starting flow or the PSI is double the starting PSI
- The max dirt capacities are determined when the flow is reduced by half the original flow (*this is the optimal operating condition*)

Recommended Viscosities

- Medium thick water-based lubricants equivalent to ISO: 46, 68, 100, 150

Harvard Corporation is able to meet many custom requirements, please contact us with you specific custom needs